



NEW!
LEXMARK X782E

Color laser multifunction printer with an easy-to-use touch screen lets you automate document processes

[Find a Reseller Near You](#)

[Support](#)
[Product Questions](#)
[View Case Studies](#)

[Interactive Demo](#)
[Product Registration](#)
[Recommended Page Volume and Duty Cycle](#)

FEATURES

AWARDS

ACCESSORIES

SPECS

Print Technology	Color Laser		
UNSPSC Code	43.21.21.05		
Display	Lexmark e-Task 8-inch (20 cm) color touch screen		
Scanner Type	Flatbed scanner with ADF		
Scan Unit Hard Disk	Yes		
Function	Color Copying Color Printing Color Scanning Faxing Color Network Scanning		
Print Speed (A4, Black): Up to	38 ppm		
Print Speed (A4, Black) Duplex: Up to	38 spm		
Print Speed (A4, Color): Up to	33 ppm		
Print Speed (Letter, Black): Up to	40 ppm		
Print Speed (Letter, Black) Duplex: Up to	40 spm		
Print Speed (Letter, Color): Up to	35 ppm		
Time to First Page (Black) As fast as	11 seconds		
Time to First Page (Color) As fast as	13 seconds		
Copy Speed (A4, Black): Up to	38 cpm		
Copy Speed (A4, Color): Up to	33 cpm		
Copy Speed (Letter, Black): Up to	40 cpm		
Copy Speed (Letter, Color): Up to	35 cpm		
Time to First Copy (Black) As fast as	< 14 seconds		
Print Resolution, Black	1200 x 1200 dpi 4800 Color Quality (2400 x 600 dpi)		
Print Resolution, Color	1200 x 1200 dpi 4800 Color Quality (2400 x 600 dpi)		
Processor	800 MHz		
Memory, Standard	768 MB		
Expandable Memory Options	No		
Memory, Maximum	768 MB		
Apple Macintosh Operating Systems Supported	Apple Mac OS X Apple Mac OS 9.x		
Microsoft Windows Operating Systems Supported	Microsoft Windows 2000 Microsoft Windows NT (4.00/4.00 Server) Microsoft Windows XP Microsoft Windows Server 2003 Microsoft Windows XP x64 Microsoft Windows Server 2003 running Terminal Server Microsoft Windows 2000 Server running Terminal Services Microsoft Windows Server 2003 x64 Edition Microsoft Windows Server 2003 x64 Edition running Terminal Services	Microsoft Windows Vista Microsoft Windows Vista x64	

	<p>Citrix MetaFrame Citrix, MetaFrame and MetaFrame XP are registered trademarks or trademarks of Citrix Systems, Inc. in the U.S. and other countries. Microsoft Windows 2000 Server running Terminal Services with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0. Microsoft Windows Server 2003 running Terminal Server with Citrix MetaFrame XP Presentation Server or Citrix MetaFrame Presentation Server 3.0. Microsoft Windows 2000 Server running Terminal Services with Citrix Presentation Server 4.0. Microsoft Windows Server 2003 running Terminal Server with Citrix Presentation Server 4.0. Microsoft Windows Server 2003 x64 Edition (Standard, Enterprise) running Terminal Server with Citrix Presentation Server 4.0</p>	<p>Paper Handling Standard 250-Sheet Output Bin 500-Sheet Drawer 500-Sheet Input Tray Duplex Unit Second 500-Sheet Drawer 100-Sheet Multipurpose Feeder</p> <p>Paper Input Capacity (Standard) 1600 pages 20 lb or 75 gsm bond</p> <p>Paper Input Capacity (Maximum) 1600 pages 20 lb or 75 gsm bond</p> <p>Paper Output Capacity (Standard) 250 pages 20 lb or 75 gsm bond</p> <p>Paper Output Capacity (Maximum) 250 pages 20 lb or 75 gsm bond</p> <p>ADF Paper Input Capacity : Up to 50 pages 20 lb or 75 gsm bond</p> <p>Finishing Option? No</p> <p>ADF Paper Output Capacity : Up to 50 pages 20 lb or 75 gsm bond</p> <p>Envelope Capacity 10</p> <p>Paper Handling Optional Banner Media Tray</p>
<p>Linux Operating Systems Supported</p>	<p>Red Flag Linux Desktop 4.0, 5.0 Linpus Linux Desktop 9.2, 9.3 Red Hat Enterprise Linux WS 3.0, 4.0, 5.0 SUSE Linux Enterprise Server 8.0, 9.0, 10.0 Debian GNU/Linux 3.1, 4.0 Linspire Linux 5.0 SUSE Linux 10.0, 10.1, 10.2</p>	<p>Number of Paper Inputs, Standard 4</p> <p>Number of Paper Inputs, Maximum 4</p> <p>Duplex (2-sided) Printing Includes Duplex Unit</p>
<p>Novell Operating Systems Supported</p>	<p>Novell® Open Enterprise Server for Netware with NDS, iPrint or Novell Distributed Print Services (NDPS) Novell NetWare® 3.2, 4.2 (bindery) Novell NetWare 4.2, 5.x and 6.x (NDS) Novell NetWare 5.x, 6.x with iPrint or Novell Distributed Print Services (NDPS)</p>	<p>Media Types Supported Card Stock Envelopes Glossy paper Labels Plain Paper Transparencies Refer to the Card Stock & Label Guide Banner Paper</p> <p>Media Sizes Supported 10 Envelope 7 3/4 Envelope 9 Envelope A4 A5 B5 Envelope C5 Envelope DL Envelope Executive Folio JIS-B5 Legal Letter Statement Universal Banner (8.27" x 36") Banner (up to 8.27" x 48")</p>
<p>Other Operating Systems Supported</p>	<p>IBM iSeries or IBM AS/400® Systems with TCP/IP with OS/400® V3R1 or later using OS/400 Host Print Transform Virtually any platform supporting TCP/IP</p>	<p>Supplies Yield 6,000*-page (CMYK) Print Cartridges 10,000*-page (CMYK) High Yield Print Cartridges 15,000*-page (CMYK) Extra High Yield Print Cartridges Ships with 10,000*-page black and color High Yield Return Program Print Cartridges *Average continuous black or continuous composite CMY declared cartridge yield up to this number of</p>
<p>UNIX Operating Systems Supported</p>	<p>Sun Solaris SPARC 8, 9, 10 HP-UX 11.00, 11.1 IBM AIX 5.1, 5.2, 5.3 Sun Solaris x86 10</p>	
<p>Web Browsers for Embedded Web Server</p>	<p>Microsoft Internet Explorer 5.x, 6.x Netscape Navigator 6.x, 7.x Apple Mac OS X Safari 1.0 Mozilla FireFox 1.0</p>	
<p>standard pages in accordance with ISO/IEC 19798.</p>		

Standard Ports	Ethernet 10/100BaseTX (RJ-45) USB Compatible with USB 2.0 Specification USB Direct interface on Operator Panel
Optional Network Ports	Lexmark N4050e 802.11g Wireless Print Server (Print Only) External MarkNet™ N7020e Gigabit Ethernet
Network Printing Methods	LPR/LPD Direct IP (Port 9100) Socket (Raw TCP/IP) IPP (Internet Printing Protocol) HTTP NDS Queue-based Printing NDPS/NEPS (Novell Distributed Print Services, Novell Netware Enterprise Print Services) Enhanced IP (Port 9400)
Network Protocol Support	TCP/IP IPv4 IPX/SPX AppleTalk™ LexLink (DLC) TCP/IP IPv6
TCP/IP Set of Application Services	Zero configuration DDNS, mDNS NTP: Network Time Protocol ping, finger, telnet TFTP
Network Management Protocols	HTTP HTTPS (SSL/TLS) SNMPv1, SNMPv2c SNMPv3 WINS SLPv1 IGMP BOOTP, RARP APIPA (AutoIP) DHCP
Network Security	SSL* Enabled Embedded Web Server SNMPv3 TCP/IP port access control 802.1x Authentication: MD5, MSCHAPv2, LEAP, PEAP, TLS, TTLS IPSec *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit.
Fonts and Symbol Sets	3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide 158 scalable PostScript fonts 2 PCL bitmap fonts 39 scalable PPDS fonts 5 PPDS bitmap fonts 84 scalable PCL fonts OCR-A, OCR-B scalable PCL 5e fonts
Printer Languages (Standard)	PCL 5c Emulation PCL 6 Emulation Personal Printer Data Stream (PPDS) PostScript 3 Emulation PDF 1.5 xHTML Direct Image
Printable Area (metric)	4.2 mm of the top, bottom, right and left edges (within)
Printable Area	0.167 inches of the top, bottom, right and left edges (within)
Reduce / Enlarge Range	25 - 400 %
Scan Area, Maximum	8.5 x 14 inches
Modem Speed	33.6 Kbps
Packaged Size (in. - H x W x D)	31.9 x 31.3 x 25.6: 49 x 48 x 40 in.
Size (in. - H x W x D)	55.5 x 26.75 x 23 in.
Weight (kg)	97.5 kg
Weight (lb.)	215 lb.
Packaged Weight (kg)	68: 81.9 kg
Packaged Weight (lb.)	150: 180.6 lb.
Noise Level, Idle	31 dBA
Print Noise Level, Operating	50 dBA
Scan Noise Level, Operating	49 dBA
Copy Noise Level, Operating	49 dBA
Product Certifications	CSA, ICES Class A, BSMI Class A, VCCI Class A, FCC Class A, UL 60950-1, IEC 60320-1, CE Class A, CB IEC 60950-1, IEC 60825-1, GS (TUV), SEMKO, UL AR, CS, TÜV Rh, C-tick mark Class A, CCC Class A