

**ML-4050N**

specifications



Function	Print
----------	-------

**Print**

Speed (Mono)	Up to 38ppm in A4 (40ppm in Letter)
First Print Out Time (Mono)	9 seconds (from Ready)
Resolution	Up to 1200 x 1200dpi effective output
Duplex	Optional
Emulation	PostScript3, PCL6, IBM ProPrinter, EPSON

**Paper Handling**

Media Size	76mm x 127mm (3" x 5") ~ 216mm x 356mm (8.5" x 14")
Media Type	Plain Paper, Transparencies, Labels, Post Card, Envelope
Input Capacity and Types	500-sheet Cassette Tray, 100-sheet Multi Purpose Tray
Output Capacity and Types	250-sheet Face Down, 100-sheet Face Up

**General**

Processor	SAMSUNG 400MHz
Memory / Storage	64MB (Max. 512MB)
OS Compatibility	Windows 98/Me/NT4.0/2000/XP (32/64bits)/Vista/2003 Server (32/64bits) Various Linux OS including Red Hat 8 ~ 9, Fedora Core 1 ~ 4, Mandrake 9.2 ~ 10.1 and SuSE 8.2 ~ 9.2, Mac OS 8.6 ~ 9.2/10.1 ~ 10.4
Interface	Hi-Speed USB 2.0, IEEE1284 Parallel, Ethernet 10/100 Base TX
Noise Level	Less than 56dBA (Printing) Less than 35dBA (Standby)
Duty Cycles, Monthly	200000 sheets
Dimension (W x D x H)	396mm x 526mm x 353mm (15.6" x 20.7" x 13.9")
Weight	17.3kg (38.14lbs)

**Consumables**

Yield	Standard: Average Cartridge Yield 10K standard pages. High Yield: Average Cartridge Yield 20K standard pages. <b>(1)</b>
Type	Single Cartridge
Model Code	ML-D4550A ML-D4550B

## Options

Options	802.11 b/g Wireless LAN (Internal), 3x500-sheet Cassette Tray, Memory : 32MB, 64MB, 128MB, 256MB, Duplex Unit, 40GB Hard Disk
---------	---

※ Features and specifications are subject to change without prior notification.

### (1) Usage note :

Declared cartridge yield in accordance with ISO/IEC 19752.



Copyright© 2008 SAMSUNG. All rights reserved.

