



PRODUCTS

Computers & Related Products

- Printer and Multifunction
- Colour Laser Printer
- Laser Printer
- Multi Function Products**
- Photo Printer
- Supplies and Accessories
- Archived Printer
- Monitor
- Optical Disk Drive
- Hard Disk Drive

Download Center
Get drivers, manuals, software and firmware

Home > Products > Computers & Related Products > Printer and Multifunction > Multi Function Products

SITE FRANÇAIS | PRODUCT REGISTRATION | SEARCH GO



+ Image View

SCX-6345N

Network ready, laser printer, digital copier, color scanner and fax in one intelligent office solution

The Samsung SCX-6345N MFP is a hard-working, high-capacity business machine. It features a monthly duty cycle of up to 200,000 pages, the option of 2180-sheet paper capacity, and print/copy speeds of up to 45 ppm. Work better with Samsung. With the SCX-6345N MFP, it's not hard to imagine.

- FAQs
- Sales Location
- Service Location

Download Center

SCX-6345N

Drivers Software Manuals

Select Model | Select Model

Features | Specifications | Solutions

Print	Method	2 Beam Laser Scanning Unit and Electro Photography
	Speed	Up to 43 ppm in A4 (45 ppm in Letter) Duplex Printing Speed: Up to 40 ipm in A4 (42 ipm in Letter)
	Resolution	Up to 1,200x1,200dpi Effective Output
	First Print Out Time	8 seconds (from Standby mode)
	Emulation	PCL6, PostScript 3
	Memory	256MB (Shared)
	Duplex Print	Standard
Copy	Speed	Up to 43 cpm in A4 (45 cpm in Letter)
	Resolution (Optical)	Scan: up to 600 x 300 (text, text/photo) up to 600 x 600 (photo using platen) up to 600 x 300 (photo using DADF) Print: up to 600 x 600 (text, text/photo, photo)
	First Copy Out Time	Less than 5 seconds
	Zoom Rate	25~400% (platen), 25~200% (ADF)
	Multy Copy	1~999
	Duplex Copy	Standard (1:2, 2:2, 2:1)
	Compatibility	Twain standard, WIA standard
Scan	Method	Color CCD
	Resolution(Optical)	600 x 600 dpi
	Resolution(Enhanced)	Max. 4,800 x 4,800 dpi
	Scan to	Email, FTP, SMB, Client
	Effective Scan Length	Platen : 348mm, DADF :348mm
	Effective Scan Width	Max 208mm(8.2")
	Color Bit depth	Internal : 36 bit, External : 24 bit
Fax	B/W Bit depth	1 bit for Text mode, 8 bit for Gray mode
	Gray Scale	256 Levels
	Compatibility	ITU-T G3, Super G3
	Applicable line	PSTN/PABX
	Modem Speed	33.6 Kbps
	Transmission Speed	Approx. 3 seconds per page
	Compression Mode	MH/MR/MMR/JBIG/JPEG
Scan Speed	Platen : Approx. 2 sec ADF : Approx. 5.5 sec Standard : 203 X 98dpi Fine : 203 X	

	Resolution	196dpi Super Fine : 203 X 391dpi, 300 X 300dpi, 406 X 392dpi
	Memory	16 MB
	Auto Dial	Speed dial : 200 Locations
	Input Capacity and Types	Main Tray : Up to 520sheets (75g/?) MP Tray : 100sheets
	Output Capacity and Types	500-sheet Face Down (75 g/?, 20 lbs)
	Media Size (for Print)	Letter, Legal, Oficio, Folio, A4, JIS B5, ISO B5, Executive, A5, Statement, A6, PostCard 4x6, Envelope B5, Envelope Monarch, Envelope COM-10, Envelope DL, Envelope C5, Envelope C6, Custom
	Media Size (for Fax and Copy)	for Fax : Letter, A4, Legal
Paper Handling	Media type	Plain Paper, Thin Paper, Bond, Punched, Pre-Printed, Recycled, Envelope, Transparency, Label, CardStock, Letterhead,Thick,Cotton,Colored,Archive
	ADF Capacity	DADF 50 sheets (20lb, 80 g/?, 0.1mm)
	ADF Document Size	Width: 174 ~ 218mm (6.9"-8.5") Length : 128 ~ 356mm (5" ~ 14.0") for Single page scan 128 ~ 400mm (5" ~ 15.7") for Multi pages scan
	Net Dimension (W x D x H)	637.4 X 489 X 616 mm
	Packing Dimension (W x D x H)	822 X 600 X 713 mm
	Weight with Consumables	44.5kg
	Packing Weight	51kg
	LCD	1/2 VGA (640x240)
	System Memory	256MB
	Interface	Hi-Speed USB 2.0, Ethernet 10/100 base TX
	OS Compatibility	Windows 98/Me/2000/XP(32/64bit)/2003 Server(32/64bit)/Vista, Various Linux OS including Red Hat 8~9, Fedora Core 1~4, Mandrake 9.2~10.1 and SuSE 8.2~9.2 Mac OS 10.3~10.4
General	Warm-up Time	Less than 35 sec from sleep mode
	Noise Level	Operating : 60 dBA @ simplex printing 62 dBA @ simplex copy Standby : 43 dBA
	Power Requirement	AC 110~127V (-10%~6%) / 6A AC 220-240V(-10%-6%) / 3A (Not convertible) 50 / 60 Hz
	Power Consumption	Sleep Mode : 35 W Standby Mode : 170 W Average : 900 W
	Operating Conditions	Temperature : 10 ~32? Humidity : 20 ~ 80%RH
	Duty Cycle, monthly Type	Up to 200,000 pages 2-piece Cartridge
	Yield	Toner : Average Cartridge Yield 20,000 standard pages Drum : 60,000 Pages; Declared yield value in accordance with ISO/IEC 19752
Consumables	Code	Toner : SCX-D6345A Drum : SCX-R6345A
	Network	Standard
Options	Others	256MB Memory: ML-MEM140 Fax Kit Serial Type: SCX-FAX100 Fax Kit Parallel Type: SCX-FAX101 Finisher: SCX-FIN10S Staple Cartridge: SCX-STP000 Stand Short Type: SCX-DSK10S Stand Tall Type: SCX-DSK10T FDI Kit: SCX-KIT10F Optional 520 sheet CST: SCX-S6345A Maintenance Kit: SCX-V6345A, SCX-V6345B

▶ The information on this page meets my needs.

Agree Disagree

| + Submit |

PRIVACY | LEGAL
© 1995 -2007 SAMSUNG. All rights reserved.